WAAS	APP CRS	Rwy Idg	6099
CH 56419	353°	TDZE	1238
W35A		Apt Elev	1258

RNAV (GPS) RWY 35

FREDERICK RGNL (FDR)

RNP APCH-GPS.

T For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -17°C or above 46°C .
A Baro-VNAV and VDP NA when using Vernon altimeter setting. When local altimeter setting not received, use Vernon altimeter setting: increase LPV DA to 1478 feet; increase LNAV/VNAV DA to 1540 feet; increase all MDAs 40 feet and visibility LNAV Cat C ¼ SM and Circling Cat D ¼ SM. Circling Rwy 3, 12,17, 21, 30, NA at night.

MISSED APPROACH: Climb to 4000 direct JIVUG and right turn on track 083° to HUNBI and right turn on track 173° to HOTEX and right turn on track 263° to FAWCI and hold.

ASOS	ALTUS APP CON *	UNICOM
132.675	125.1 353.7	123.05 (CTAF) L



ELEV 1258 TDZE 1238





CATEGORY	A	B	C	D
LPV DA	1438-¾ 200 (200-¾)			
LNAV/VNAV DA	1500-1 262 (300-1)			
LNAV MDA	1600-1 362 (400-1)			1600-1¼ 362 (400-1¼)
CIRCLING	1700-1 442 (500-1)	1720-1 462 (500-1)	1880-1¾ 622 (700-1¾)	1900-2 642 (700-2)

SC-1, 11 JUN 2026 to 09 JUL 2026
SC-1, 11 JUN 2026 to 09 JUL 2026