

WAAS CH 86622 W13A	APP CRS 136°	Rwy Idg TDZE 642 Apt Elev 660
--	------------------------	---

RNAV (GPS) RWY 13

PERRY COUNTY MUNI (TEL)



▼

▲ NA

When VGSI inop, Circling Rwy 31 NA at night. When VGSI inop, Straight-in/Circling Rwy 13 procedure NA at night. DME/DME RNP-0.3 NA. Visibility reduction by helicopters NA. Obtain local altimeter setting on CTAF; when not received, use Huntingburg altimeter setting and increase all MDA 80 feet and increase LP Cat C visibility ¼ mile and LNAV Cat C visibility ⅓ mile.

MISSED APPROACH:
Climb to 2500 direct FOMUV and hold.

EVANSVILLE APP CON ★ 124.025 290.9	UNICOM 122.7 (CTAF) 0
--	---------------------------------



CATEGORY	A	B	C	D
LP MDA	1000-1	358 (400-1)	1000-1⅓ 358 (400-1⅓)	NA
LNAV MDA	1040-1	398 (400-1)	1040-1¼ 398 (400-1¼)	NA
CIRCLING	1080-1 420 (500-1)	1120-1 460 (500-1)	1120-1½ 460 (500-1½)	NA

ELEV 660 TDZE 642

136° to RWY 13

1.2% Up

4400 X 75

REIL Rwy 13 and 31 0
MIRL Rwy 13-31 0