

WAAS
CH **77809**
W16A

APP CRS
163°

Rwy Ldg
TDZE **1803**
Apt Elev **1803**

RNAV (GPS) RWY 16
AURORA MUNI/AL POTTER FLD (AUH)

Baro-VNAV NA when using Grand Island altimeter setting. For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -18°C (0°F) or above 54°C (130°F). DME/DME RNP-0.3 NA. Visibility reduction by helicopters NA. When local altimeter setting not received, use Grand Island altimeter setting and increase all DA 41 feet and all MDA 60 feet and LPV all Cals visibility ¼ mile. VDP NA when using Grand Island altimeter setting.

MISSED APPROACH:
Climb to 3400 direct EBWIX and hold.

AWOS-3 121.225	MINNEAPOLIS CENTER 119.4 278.8	UNICOM 122.8 (CTAF) 0
--------------------------	--	---------------------------------

Procedure NA for arrival on GRI VOR/DME airway radials 077 CW 108.

MISSED APCH FIX

EBWIX

MSA RW16 25 NM

4100

4 NM Holding Pattern

CEGIT

FOBDO

CAKAY 2 NM to RW16

3400

EBWIX

GP 3.00° TCH 40

*2480

*1 NM to RW16

RW16

*LNAV only

ELEV 1803

TDZE 1803

163°

91

4301 X75

1852 ±

34

MIRL Rwy 16-34 0

CATEGORY	A	B	C	D
LPV DA	2102-1	299 (300-1)	NA	
LNAV/VNAV DA	2133-1¼	330 (400-1¼)	NA	
LNAV MDA	2160-1	357 (400-1)	NA	
CIRCLING	2300-1 497 (500-1)	2340-1 537 (600-1)	NA	

AURORA, NEBRASKA

Amdt 1B 13AUG20

40°54'N-98°00'W

AURORA MUNI/AL POTTER FLD (AUH)

RNAV (GPS) RWY 16