

WAAS CH 58332 W19A	APP CRS 186°	Rwy Ldg TDZE 522 Apt Elev 522
--	------------------------	---

RNAV (GPS) RWY 19
MAYFIELD GRAVES COUNTY (M25)

RNP APCH - GPS.



▼


⚠

Circling Rwy 1 NA at night. Rwy 19 helicopter visibility reduction below ¾ SM NA. Baro-VNAV NA when using Paducah altimeter setting. For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -16°C or above 54°C. When local altimeter setting not received, use Paducah altimeter setting: increase LPV DA to 833 feet, LNAV/VNAV DA to 977 feet and all visibilities ¼ SM; increase all MDAs 80 feet and visibility Cats C and D ¼ SM.

MISSED APPROACH:
Climb to 2300 direct LUXON and hold.

AWOS-3 120.625	MEMPHIS CENTER 133.65 292.15	UNICOM 122.8 (CTAF) 0
--------------------------	--	---------------------------------



2300	LUXON	VGSI and RNAV glidepath not coincident (VGSI Angle 3.00/TCH 35).				6 NM Holding Pattern	
		YOPKU 1.4 NM to RW19	CITBY 2400	JOELY	186°	006° → 6000 ← 186° 2400	GP 3.00° TCH 56
		1020	2400				
CATEGORY		A	B	C	D		
LPV DA	772-1 250 (300-1)						
LNAV/ VNAV DA	916-1½ 394 (400-1½)						
LNAV MDA	880-1 358 (400-1)						
CIRCLING	1060-1 538 (600-1)			1060-1½ 538 (600-1½)		1280-2½ 758 (800-2½)	

SE-1, 09 JUL 2026 to 06 AUG 2026

SE-1, 09 JUL 2026 to 06 AUG 2026