


WAAS CH 58033 W16A	APP CRS 159°	Rwy Ldg TDZE Apt Elev	4007 1368 1368
--	------------------------	-----------------------------	---

RNAV (GPS) RWY 16

WADENA MUNI (ADC)

RNP APCH - GPS.	
Baro-VNAV and VDP NA when using SAZ altimeter setting. Rwy 16 helicopter visibility reduction below ¾ SM NA. Circling NA to Rwy 3 and 21. For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -17°C or above 54°C. When local altimeter setting not received, use SAZ altimeter setting and increase LPV DA to 1682 feet; increase LNAV/VNAV DA to 1811 feet and all visibilities ¼ SM. Increase all MDAs 60 feet and LNAV visibility Cat C ¼ SM, and Circling visibility Cat C ¼ SM.	MISSED APPROACH: Climb to 3300 direct JOLIT and hold.

AWOS-3PT 118.875	MINNEAPOLIS CENTER 126.1 269.2	GCO 121.725	UNICOM 122.8 (CTAF) 0
----------------------------	--	-----------------------	---------------------------------



4 NM Holding Pattern		WENVI	DIXGY	ZOBED	JOLIT
6000 ← 339°		3300 → 159°	3000	1.8 NM to RW16	3300
GP 3.00°		3000	1.1 NM to RW16	RW16	JOLIT
TCH 42		1980	0.7	1.1 NM	
8 NM		3.2 NM	0.7	1.1 NM	
CATEGORY	A	B	C	D	
LPV DA	1631-1 263 (300-1)			NA	
LNAV/VNAV DA	1760-1 392 (400-1 ½)			NA	
LNAV MDA	1760-1 392 (400-1)		1760-1 392 (400-1 ½)	NA	
CIRCLING	1780-1 412 (500-1)	1820-1 452 (500-1)	1940-1 572 (600-1 ½)	NA	

