


APP CRS	Rwy Idg	5001
093°	TDZE	790
	Apt Elev	790

RNAV (GPS) RWY 9

BULT FLD (C56)

NA DME/DME RNP-0.3 NA. Visibility reduction by helicopters NA. Use Lansing Muni altimeter setting; when not received, use Chicago Midway Intl altimeter setting and increase all MDA 40 feet. Procedure NA at night.	MISSED APPROACH: Climbing right turn to 2600 direct EON VORTAC and hold.
---	---

AWOS-AV 119.125	IGQ AWOS-3PT 124.925	CHICAGO CENTER 132.5 284.7	UNICOM 123.0 (CTAF)
--------------------	-------------------------	-------------------------------	------------------------



4 NM Holding Pattern HOSIX AGREE 2600 EON			
2300 273° 093° 2300 093° 2300 3.04° TCH 40 SEFOB 2.5 NM to RW09 1620 RW09			
6.1 NM 2.1 NM 2.5 NM			
CATEGORY	A	B	C
LNNAV MDA	1220-1	430 (500-1)	1220-1¼ 430 (500-1¼)
CIRCLING	1260-1 470 (500-1)	1400-1½ 610 (700-1½)	1400-1¾ 610 (700-1¾)
NA NA			