

25331


RNAV (GPS) RWY 25

BOB BAKER MEML (IAN) (PAIK)


 Circling NA north of Rwy 7-25. Circling Rwy 7 NA at night. For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -25°C or above 54°C. Baro-VNAV and VDP NA when using WLK/PASK altimeter setting. When local altimeter setting not received, use WLK/PASK altimeter setting and increase LPV DA* to 531 feet; increase LPV DA to 720 feet and all visibilities ¼ SM. Increase LNAV/VNAV DA to 888 feet and all visibilities ¼ SM. Increase all MDAs 100 feet.

MISSED APPROACH: Climb to 900 then climbing left turn to 4000 direct KOBXU and hold, continue climb-in-hold to 4000.
*Missed approach requires minimum climb of 335 feet per NM to 1440.

AWOS-3P 119.025	ANCHORAGE CENTER 119.2 263.0	CTAF 122.7
--------------------	---------------------------------	---------------



ELEV 179
TDZE 175



900 4000 KOBXU

VGSI and RNAV glidepath not coincident (VGSI Angle 3.00°/TCH 29).

LETMY RELOC 5 NM Holding Pattern

UCANE 2900

4.9 NM to RWY25

253° 253° 254° 074° 10000 4500

3300 2900

GP 3.00° TCH 35

4.9 NM 3.7 NM 1.9 NM 5.6 NM

CATEGORY	A	B	C	D
LPV DA*	450-1 275 (300-1)			
LPV DA	639-1 $\frac{3}{8}$ 464 (500-1 $\frac{3}{8}$)			
RNAV/VNAV DA	807-1 $\frac{3}{4}$ 632 (700-1 $\frac{3}{4}$)			
RNAV MDA	1740-1 $\frac{1}{4}$ 1565 (1600-1 $\frac{1}{4}$)	1740-1 $\frac{1}{2}$ 1565 (1600-1 $\frac{1}{2}$)	1740-3	1565 (1600-3)
CIRCLING	1740-1 $\frac{1}{4}$ 1561 (1600-1 $\frac{1}{4}$)	1740-1 $\frac{1}{2}$ 1561 (1600-1 $\frac{1}{2}$)	1740-3	1561 (1600-3)

BOB BAKER MEML (IAN) (PAIK)
RNAV (GPS) RWY 25

AK, 09 JUL 2026 to 03 SEP 2026