

WAAS CH 42600 W04A	APP CRS 043°	Rwy Ldg TDZE Apt Elev	5764 2634 2634
--	------------------------	-----------------------------	---

RNAV (GPS) RWY 4
FRANK WILEY FLD (MLS)

RNP APCH-GPS.


▼

⚠


For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -25°C or above 54°C. When local altimeter setting not received, use Glendive altimeter setting: increase LPV and LNAV/VNAV DA to 3051 and all visibilities ½ SM. Increase all MDA 180 feet and LNAV Cat C and D visibilities ¾ SM and Circling Cat C and D visibilities ½ SM. Baro-VNAV and VDP NA when using Glendive altimeter setting.

MISSED APPROACH: Climb to 6000 direct AXUPE and hold, continue climb-in-hold to 6000.

ASOS 135.575	SALT LAKE CENTER 126.85 305.2	UNICOM 123.0 (CTAF) 1
------------------------	---	---------------------------------



5 NM Holding Pattern		OPEJY	UCVIC	YULUT	AXUPE
9000		5600	4300	3400	6000
GP 3.00°		TCH 40	6.8 NM	2.8 NM	1.2 NM
CATEGORY	A	B	C	D	
LPV DA	2884-1		250 (300-1)		
LNAV/VNAV DA	2884-1		250 (300-1)		
LNAV MDA	3040-1	406 (500-1)	3040-1 1/8	406 (500-1 1/8)	
CIRCLING	3060-1 426 (500-1)	3100-1 466 (500-1)	3160-1 1/2 526 (600-1 1/2)	3320-2 1/4 686 (700-2 1/4)	



NW-1, 01 OCT 2026 to 29 OCT 2026

NW-1, 01 OCT 2026 to 29 OCT 2026