

LOC/DME I-JDL	APP CRS	Rwy Ldg	8457
109.9	071°	TDZE	25
Chan 36		Apt Elev	25

LDA X RWY 8
JUNEAU INTL (JNU)(PAJN)

ADF required.

▼

▲


1°C

Circling to Rwy 26 NA at night. Circling NA north of Rwy 8-26. Rwy 8 helicopter visibility reduction below 1 SM NA. Inop table does not apply. When Juneau altimeter setting not received, procedure NA. CAUTION: Any go-around after passing MAP will not provide standard obstruction clearance. Circling Cat A night visibility minimum 5 SM, Circling Cat B, C, D night visibility minimum 10 SM. Straight-in Rwy 8 at night, operational VGSI required, remain on or above VGSI glidepath until threshold.

MALSF

MISSED APPROACH: Immediate climbing right turn to 5600 on heading 310° and on CGL NDB bearing 251° to intercept SSR VORTAC R-027 direct SSR VORTAC or EEF NDB and hold.

ATIS 135.2	ANCHORAGE CENTER 133.9	JUNEAU TOWER ★ 118.7 (CTAF) 0 278.3	GND CON 121.9	JUNEAU RADIO 122.2
---------------	---------------------------	--	------------------	-----------------------



LYNNS I-JDL 14

5600

SSR R-027

EEF

071°

TWR

8857 X 1.50

4800 X 1.50

200

200

200

Remain within 10 NM

251°

DIBOL I-JDL 18

6300

071°

6300

5600

3700

4 NM

6 NM

6 NM

3.2 NM

Use I-JDL DME when on LDA course.

CATEGORY

A

B

C

D

S-LDA 8

3200-4

3175 (3200-4)

NA

CIRCLING

3200-4

3175 (3200-4)

3340-4

3315 (3400-4)

3700-4

3675 (3700-4)

RLS Rwy 8

REIL Rwy 26 0

HIRL Rwy 8-26 0

AK, 03 SEP 2026 to 29 OCT 2026

AK, 03 SEP 2026 to 29 OCT 2026