

LOC/DME I-ONA 109.35 Chan 30 (Y)	APP CRS 300°	Rwy Ldg 5199 TDZE 656 Apt Elev 656
--	------------------------	---

ILS Y or LOC Y RWY 30
WINONA MUNI/MAX CONRAD FLD (ONA)

DME required.

 VDP NA with La Crosse allimeter setting. When local allimeter setting not received, use La Crosse allimeter setting and increase S-ILS 30 DA to 1127 and all visibilities ½ mile, increase all MDA 60 feet, and visibility S-LOC 30 Cat C/D ½ mile, and Circling Cat B ¼ mile. For inop ALS, increase S-ILS 30 all Cats visibility to 1½ mile, increase S-LOC 30 Cats C/D visibility to 1 ½ mile. For inop ALS when using La Crosse allimeter setting, increase S-ILS 30 all Cats visibility to 1½ mile, increase S-LOC 30 Cats C/D visibility to 1 ½ mile.

MALS^R

MISSED APPROACH:
Climb to 1800 then
climbing left turn to
3000 on RST VOR/
DME R-056 to VUZID
INT and hold.

AWOS-3 118.075	MINNEAPOLIS CENTER 128.6 363.0	UNICOM 122.8 (CTAF) 0
--------------------------	--	---------------------------------

