


WAAS CH 69630 W05A	APP CRS 050°	Rwy Ldg TDZE 3427 Apt Elev 3443
--	------------------------	---

RNAV (GPS) RWY 5
SHELBY (SBX)

RNP APCH - GPS.	MISSED APPROACH: Climb to 9000 direct YENUP and hold, continue climb-in-hold to 9000.
Baro-VNAV and VDP NA when using Cut Bank altimeter setting. For uncompensated Baro-VNAV systems, UNAV/VNAV NA below -21°C or above 54°C. When local altimeter setting not received, use Cut Bank altimeter setting.	

AWOS-3PT 128.325	SALT LAKE CITY CENTER 133.4 285.4	UNICOM 122.8 (CTAF) 0
----------------------------	---	---------------------------------



7 NM Holding Pattern				
14000 7000 230° 050°				
GP 3.00° TCH 45				
CAVBU 5100 050° 5100 4300 7 NM 2.4 NM 1.6 NM 1.1 NM				
VGSI and RNAV glidepath not coincident (VGSI Angle 3.00/TCH 29).				
9000 YENUP				
CATEGORY	A	B	C	D
LPV DA		3733-1	306 (300-1)	
UNAV/VNAV DA		3783-1	356 (400-1)	
UNAV MDA		3800-1	373 (400-1)	
CIRCLING	4020-1 577 (600-1)	4080-1 637 (700-1)	4100-1¾ 657 (700-1¾)	4220-2½ 777 (800-2½)

