


LOC/DME I-LWR 110.7 Chan 44	APP CRS 180°	Rwy Ldg TDZE 213 Apt Elev 213
---	------------------------	---


ILS or LOC RWY 17

WEST MEMPHIS MUNI (A W M)

DME or RADAR required.	MALSR
NA For inop ALS, increase S-LOC 17 Cat C/D visibility to 1½ SM and KEHOE FIX MINIMUMS S-LOC 17 Cats C/D visibility to 1 SM.	MISSED APPROACH: Climb to 1000 then climbing right turn to 2000 on GQE VOR/DME R-147 to GQE VOR/DME and hold.

ASOS 118.175	MEMPHIS APP CON 119.1 291.6	CLNC DEL 121.7	UNICOM 123.05 (CTAF) 0
------------------------	---------------------------------------	--------------------------	---



1000 ↑	2000 GQE R-147	GQE 	DANNZ I-LWR 6.7 RADAR		PALYN INT I-LWR 12.7 RADAR
*LOC only.			KEHOE I-LWR 2.7 RADAR		
I-LWR 1.3 			GS 3.00° TCH 51		
CATEGORY	A		B	C	D
S-ILS 17	413-½ 200 (200-½)				
S-LOC 17	680-½ 467 (500-½)		680-1 467 (500-1)		
CIRCLING	680-1 467 (500-1)	740-1 527 (600-1)	800-1½ 587 (600-1½)	920-2¼ 707 (800-2¼)	
KEHOE FIX MINIMUMS					
S-LOC 17	580-½ 367 (400-½)		580-5⁄8 367 (400-5⁄8)		
CIRCLING	640-1 427 (500-1)	740-1 527 (600-1)	800-1½ 587 (600-1½)	920-2¼ 707 (800-2¼)	

