

WAAS CH 86505 W06A	APP CRS 057°	Rwy Ldg TDZE Apt Elev	5000 303 303
--	------------------------	-----------------------------	---

RNAV (GPS) RWY 6


WOODWARD FLD (CDN)

RNP APCH - GPS.

▼ Baro-VNAV and VDP NA when using CAE altimeter setting. When local altimeter setting not received, use CAE altimeter setting: increase LPV DA to 673 feet; increase LNAV/VNAV DA to 804 feet; increase all MDAs 100 feet and LNAV visibility Cat C ¼ SM, LNAV visibility Cat D ½ SM, and Circling visibility Cats C/D ½ SM. For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -15°C or above 54°C. Circling Rwy 14, 32 NA at night.

MISSED APPROACH:
Climb to 3000 direct
IBAYE and hold.

AWOS-3PT 119.975	SHAW APP CON ★ 125.4 318.1	UNICOM 123.0 (CTAF) 0
----------------------------	--------------------------------------	---------------------------------



5 NM Holding Pattern		YESLU		WEVEX		1.5 NM to RW06		3000 ↑		IBAYE ✱	
3700 ←237° 057°→				057°		2000					
GP 3.00° TCH 31											
		6.1 NM		3.8 NM		1.5 NM					
CATEGORY		A	B	C	D						
LPV DA	583-1 280 (300-1)										
LNAV/ VNAV DA	714-1½ 411 (500-1½)										
LNAV MDA	780-1	477 (500-1)	780-1⅜ 477 (500-1⅝)		780-1½ 477 (500-1½)						
CIRCLING	840-1	537 (600-1)	840-1½ 537 (600-1½)		900-2 597 (600-2)						

