

WAAS
CH **93920**
W31A

APP CRS
308°

Rwy Ldg
TDZE **1123**
Apt Elev **1123**

4010

1123

1123

RNAV (GPS) RWY 31

LITTLE FALLS/MORRISON COUNTY-LINDBERGH FLD (LXL)

RNP APCH - GPS.

▼

Baro-VNAV NA when using STC altimeter setting. For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -17°C or above 32°C. Rwy 31 visibility reduction below ¾ SM by helicopters NA. When local altimeter setting not received, use STC altimeter setting and increase all DAs 76 feet and all MDAs 80 feet; increase LPV all Cats visibility ½ SM and LNAV/VNAV all Cats, LNAV Cat C/D and Circling Cat C/D visibility ¼ SM. Circling Rwy 18, 36 NA.

▲

MISSED APPROACH:
Climb to 3000 direct ZUGUT and hold.

AWOS-3 119.45	MINNEAPOLIS CENTER 118.05 239.0	GCO 121.725	UNICOM 122.8 (CTAF) 0
-------------------------	---	-----------------------	---------------------------------

MISSED APCH FIX

ZUGUT

128°

308°

4 NM

RW31

1409 ±

(FAF) TUNCI

2800

308°

(6.1)

128°

308°

4 NM

Procedure NA for arrivals at GOLLF on V82-161 southbound.

4000 NoPT

280°

(18.9)

(IAF) GOLLF

MSA RW31 25 NM

3300

Procedure NA for arrivals at SIYON on V510 westbound.

SIYON

4000

045°

(9.2)

(IF/IAF) URENE

Procedure NA for arrivals at DAYLE on V413 southbound.

DAYLE

4000 NoPT

321°

(1.5)

(IAF) DAYLE

ELEV 1123

TDZE 1123

3000

ZUGUT

VGSI and RNAV glidepath not coincident (VGSI Angle 3.00/TCH 25).

4 NM Holding Pattern

TUNCI

2800

URENE

2800

RW31

2800

128°

308°

4000

GP 3.00°

TCH 45

5.1 NM

6.1 NM

CATEGORY	A	B	C	D
LPV DA	1517-1⅜		394 (400-1⅜)	
LNAV/VNAV DA	1749-2¼		626 (700-2¼)	
LNAV MDA	1660-1	537 (600-1)	1660-1½	537 (600-1½)
CIRCLING	1700-1 577 (600-1)	1800-1 677 (700-1)	1840-2 717 (800-2)	2000-2¾ 877 (900-2¾)

LIRL Rwy 18-36 0

MIRL Rwy 13-31 0

REIL Rws 13 and 31 0

LITTLE FALLS, MINNESOTA

LITTLE FALLS/MORRISON COUNTY-LINDBERGH FLD (LXL)

Orig-E 09JUL26

45°57'N-94°21'W

RNAV (GPS) RWY 31