

WAAS CH 72940 W14A	APP CRS 142°	Rwy Ldg TDZE 44 Apt Elev 45
--	------------------------	---

RNAV (GPS) RWY 14

EASTPORT MUNI (EPM)

RNP APCH - GPS.


▼

⚠ NA

For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -15°C or above 54°C. Baro-VNAV and VDP NA when using BHB altimeter setting. Rwy 14 helicopter visibility reduction below ¾ SM NA. When local altimeter setting not received, use BHB altimeter setting and increase LPV DA to 462 feet and all visibilities ½ SM. Increase LNAV/VNAV DA to 565 feet and all visibilities ½ SM. Increase all MDAs 160 feet and LNAV visibility Cat C/D ¾ SM, and Circling visibility Cat C/D ¾ SM.

MISSED APPROACH: Climb to 520 then climbing right turn to 4000 direct PIERR and hold, continue climb-in-hold to 4000.

AWOS-AV 122.8	BOSTON CENTER 124.25 290.5	UNICOM 122.8 (CTAF) 0
-------------------------	--------------------------------------	---------------------------------



4 NM Holding Pattern		PIERR		KEAND		CAXIX		RW14	
6000 4000		322° 142°		1600		820		1.3 NM to RW14	
GP 3.10° TCH 53		7.9 NM		2.4 NM		0.9 NM		1.3 NM	
CATEGORY	A	B	C	D					
LPV DA	309-1		265 (300-1)						
LNAV/ VNAV DA	412-1		368 (400-1)						
LNAV MDA	520-1	476 (500-1)	520-1 3/8	476 (500-1 3/8)					
CIRCLING	620-1	575 (600-1)	640-1 1/2 595 (600-1 1/2)	820-2 1/2 775 (800-2 1/2)					

ELEV 45 TDZE 44

520

4000

PIERR

142°

0.3% UP

4002 X 75

32

MIRL Rwy 14-32 0
REIL Rwy 14 and 32 0

NE-1, 01 OCT 2026 to 29 OCT 2026

NE-1, 01 OCT 2026 to 29 OCT 2026