

WAAS CH 56538 W18A	APP CRS 181°	Rwy Ldg 5002 TDZE 845 Apt Elev 845
--	------------------------	---

RNAV (GPS) RWY 18

NORTH CENTRAL MISSOURI RGNL (M08)

RNP APCH.



▼

▲ NA

For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -16°C or above 54°C. Baro-VNAV and VDP NA when using Kirksville altimeter setting. When local altimeter setting not received, use Kirksville altimeter setting and increase LPV and LNAV/VNAV DA all Cats to 1179 feet and increase visibility 1⁄8 mile all Cats; increase all MDA 100 feet and increase LNAV Cat C/D visibility 3⁄8 mile and Circling Cat C visibility 1⁄4 mile. Rwy 18 helicopter visibility reduction below 3⁄4 SM NA.

MISSED APPROACH:
Climb to 3000 direct
CUKIT and hold.

AWOS-2 118.425	KANSAS CITY CENTER 125.25 235.975	CTAF 122.9 0
--------------------------	---	------------------------



3000 ↑	CUKIT 	COROS 4 NM Holding Pattern		
*LNAV only	*1.5 NM to RW18	TRULL 2900	001° → ← 181° 3000	
RW18	1.5	4.8 NM	6 NM	
		181°	2900	
		GP 3.00° TCH 40		
CATEGORY	A	B	C	D
LPV DA	1095-1		250 (300-1)	
LNAV/VNAV DA	1095-1		250 (300-1)	
LNAV MDA	1360-1	515 (600-1)	1360-1 3⁄8	515 (600-1 3⁄8)
CIRCLING	1360-1	515 (600-1)	1360-1 1⁄2 515 (600-1 1⁄2)	1400-2 555 (600-2)