

WAAS CH 97729 W12A	APP CRS 122°	Rwy Ldg TDZE Apt Elev	3900 2252 2264
--	------------------------	-----------------------------	---

RNAV (GPS) RWY 12


SHER-WOOD (PWD)

RNP APCH-GPS.

Circling Rwy 8, 26 NA at night. For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -19°C or above 54°C. When local altimeter setting not received, use Williston altimeter setting.

MISSED APPROACH: Climb to 5000 direct BEYYA and hold.

AWOS-3PT 135.025	SALT LAKE CENTER 126.85 305.2	UNICOM 122.8 (CTAF) 0
----------------------------	---	---------------------------------



VGSI and RNAV glidepath not coincident (VGSI Angle 3.00/TCH 28).					5000	BEYYA
5 NM Holding Pattern		WODOS	OWFEW	IHHIB		
6000 ← 259°			3900	2.3 NM to RW12		
4000 → 079°						
GP 3.00°			3900	122°	1.2 NM to RW12	
TCH 44				3020		
		4 NM	2.7 NM	1.1 NM	1.2 NM	
						
CATEGORY	A	B	C	D		
LPV DA	2567-7/8 315 (400-7/8)					
LNAV/VNAV DA	2617-1 365 (400-1)					
LNAV MDA	2660-1	408 (400-1)	2660-1 1/8		408 (400-1 1/8)	
CIRCLING	2780-1	516 (600-1)	2880-1 3/4 616 (700-1 3/4)		3100-2 3/4 836 (900-2 3/4)	

