NDB ICW	APP CRS	Rwy Ldg	4600
525	056°	TDZE	368
		Apt Elev	368


NDB RWY 4L

NENANA MUNI (ENN) (PANN)

Procedure NA at night. Circling NA northwest of Rwy 4L-22R. Circling NA to Rwys 4R, 22L, 4W and 22W. Rwy 4L helicopter visibility reduction below 1 SM NA. When local altimeter setting not received, use FAI/PAFA altimeter setting and increase all MDAs 100 feet and S-4L visibility Cats C and D ¼ SM, and Circling visibility Cats C and D ¼ SM.

MISSED APPROACH: Climbing right turn to 3200 on ICW NDB bearing 130°, then left turn direct ICW NDB and hold.

ASOS	FAIRBANKS APP CON	FAIRBANKS RADIO	CTAF
125.2	125.35 363.2	122.5	122.1 L



CATEGORY	A	B	C	D
S-4L	1000-1	632 (700-1)	1000-1¾	632 (700-1¾)
CIRCLING	1000-1	632 (700-1)	1140-2¼ 772 (800-2¼)	1140-2½ 772 (800-2½)

REIL Rwys 4L and 22R L
MIRL Rwys 4L-22R L
MIRL Rwys 4R-22L

AK, 29 OCT 2026 to 24 DEC 2026
AK, 29 OCT 2026 to 24 DEC 2026